



Sturdo
RESTROOM CUBICLES & LOCKERS



Shower Room Solutions

BOQ - SHOWER VISION BARRIER

BOQ -SHOWER VISION BARRIER

Client:	
Project:	
Location:	
Title:	Date:
Rev Dt.:	Rev No.:

BILL OF QUANTITIES FOR TOILET BLOCK WORK

Sr No.	Item Description	Approved Make	Floors	Quantity	Unit	Basic Price	Total Amount
1.00	PARTITIONS AND ASSOCIATED WORKS						
1.00	Shower Vision Barrier						
	<p>"Providing & fixing Greenlam Sturdo Shower Vision Barrier self-supporting 12mm thick compact laminates made out of, urea free, thermosetting phenolic resins treated Kraft papers as core material and Amino plastic resin treated decor papers on the finish surface, conforming to latest and applicable IS: 2046-1995, EN 438:2016 and NEMA LD3-2005 quality standards with Antivirus, Antibacterial and Antifungal properties (conforming to ISO 21702:2019, JIS Z2801:2010 and ASTM G21-2015 standards respectively) to fulfil the applicable requirements of indoor air quality certifications for Greenguard-Gold standards.</p> <p>This also includes providing and fixing in position necessary hardware made out of Stainless steel/Nylon Polyamide grade 6 & Aluminium alloy grade 6063-T6 powder coated finish in black and other available color hardwares as per manufacturer's specifications & Architects instructions like (1) Double Coat hook made in SS 316 in SS brushed finish with fine spark texture on nylon parts (2) U & F- profiles in Aluminium alloy grade 6063-T6 with powder coating in available colors (3) SS grade 316/Nylon divider mounted sleek leg with Ground Clearance (120-150mm) (4) Aligning SS grade 316 common top rail 25.4mm diameter round pipe fixed with wall connector made of 316 grade stainless steel in brushed finish (5) Screws & wall Plugs (SS- 316).</p> <p>Available Design Options 1)-Loop In : 12mm thick compact with minimal wall touch divider of size 730mm(D) x 1830(H) with ground clearance of 150mm mounted on sleek leg, fixed with bracket, hence higher hygiene quotient. With In-built hook design feature within dividers for improved utility. 2)-Loop Out : 12mm thick compact divider with straight edge of size 730mm(D) x 1830(H) with ground clearance of 150mm mounted on sleek leg, fixed with U profiles of size 18mmx16mm.</p> <p>All screws will be of 316 Grade in stainless steel . All pilasters are supported by grade- 6 Nylon Polyamide Thermoplastic palm design pedestal footing with non corrosive steel inserts. The base anchored to the floor with grade 316 satin finish stainless steel screws with push fit capping at a clearance height of 150mm. "</p>	Shower Vision Barrier Of Greenlam Sturdo			No.	0	