



Sturdo  
RESTROOM CUBICLES & LOCKERS



*Test Reports*

**BSEN TEST REPORT**

**Test Report No. 7191005793-MEC11-TYW**  
dated 30 MAY 2011



PSB Singapore

**Note:** This report is issued subject to TÜV SÜD PSB's "Terms and Conditions Governing Technical Services".  
The terms and conditions governing the issue of this report are set out as attached within this report.

**SUBJECT:**

Testing of Laminated Board Samples


**TESTED FOR:**

Greenply Industries Ltd  
1501-1505 Narain manzil  
23 Barakamba Road  
New Delhi, India 110001  
India

Attn: Mr Rakesh Budhiraja

**SAMPLES DESCRIPTION:**

The following Laminated Board Samples were submitted by Greenply Industries Ltd on 20 April 2011 for testing.

Laminated Board samples	Approximate Dimensions	Quantity
	50 mm x 50 mm x 12 mm	12 pcs
	100mm x 100mm x 12mm	4 pcs
	100mm x 100mm x 12mm (with 6.9mm hole at the centre)	6 pcs
	230 mm x 230 mm x 12 mm	13 pcs
	250 mm x 250 mm x 12 mm	4 pcs
	250 mm x 50 mm x 12 mm	16 pcs
	70 mm x 70 mm x 12 mm	10 pcs
	100mm x 80mm x 12mm	6 pcs



**Laboratory:**  
**TÜV SÜD PSB Pte. Ltd.**  
No.1 Science Park Drive  
Singapore 118221

Phone : +65-6885 1333  
Fax : +65-6776 8670  
E-mail: testing@tuv-sud-psb.sg  
www.tuv-sud-psb.sg  
Co. Reg : 199002667R

**Regional Head Office:**  
**TÜV SÜD Asia Pacific Pte. Ltd.**  
3 Science Park Drive, #04-01/05  
The Franklin, Singapore 118223  
**TUV®**

*Wah Lishy*

**TEST METHODS:**

**BS EN 438-2 : 2005**

**High-pressure decorative laminates (HPL) - Sheets based on thermosetting resins (Usually called Laminates) - Part 2 : Determination of properties**


1. Determination of thickness  
Nominal specimen dimensions : 50mm x 50mm x 12mm  
No. of determinations : 2
2. Resistance to surface wear  
Nominal specimen dimensions : 100mm x 100mm x 12mm  
(with a hole of 6mm at the centre)  
No. of determinations : 2
3. Resistance to immersion in boiling water  
Nominal specimen dimensions : 50mm x 50mm x 12mm  
No. of determinations : 3
4. Resistance to water vapour  
Nominal specimen dimensions : 50mm x 50mm x 12mm  
No. of determinations : 1
5. Resistance to dry heat  
Nominal specimen dimensions : 230mm x 230mm x 12mm  
No. of determinations : 1
6. Dimensional stability at elevated temperature  
Nominal specimen dimensions : 250mm x 250mm x 12mm  
No. of determinations : 8
7. Dimensional stability at ambient temperature  
Nominal specimen dimensions : 250mm x 250mm x 12mm  
No. of determinations : 8
8. Resistance to impact by large diameter ball  
Nominal specimen dimensions : 230mm x 230mm x 12mm  
No. of determinations : 5
9. Resistance to crazing (Compact laminates)  
Nominal specimen dimensions : 230mm x 230mm x 12mm  
No. of determinations : 2
10. Resistance to Staining  
Nominal specimen dimensions : 250mm x 250mm x 12mm  
Reagent used : a) Acetone (16h)  
b) Coffee (16h)  
c) 25% Sodium Hydroxide (10min)  
d) 30% Hydrogen Peroxide (10min)  
e) Shoe Polish (10min)  
No. of determinations : 2
11. Lightfastness (xenon arc)  
Nominal specimen dimensions : 100 mm x 80 mm x 12 mm  
Duration : 100 hrs  
No. of determinations : 1
12. Resistance to cigarette burns  
Nominal specimen dimensions : 230 mm x 230 mm x 12 mm  
No. of determinations : 1


*Wah Lishy*



**TEST RESULTS:**

S/N	Characteristics	Unit	Results / Observations
1.	Determination of thickness	mm	12.19
2.	Resistance to surface wear	revolution	1150
3.	Resistance to immersion in boiling water	% % -	0.6 (increase in mass) 0.3 (increase in thickness) Rating 5 : no visible change in appearance
4.	Resistance to water vapour	-	Rating 5 : No visible change.
5.	Resistance to dry heat	-	Rating 5 : No visible change
6.	Dimensional stability at elevated temperature	%	0.15 (Machine Direction) 0.05 (Cross- machine Direction)
7.	Dimensional stability at ambient temperature	%	0 (Machine Direction) 0.05 (Cross- machine Direction)
8.	Resistance to impact by large diameter ball	-	No visible surface cracking was observed at 3 meters
9.	Resistance to crazing (Compact laminates)	-	Rating 5 : Surfaces and edges unchanged from 'as received' condition
10.	Resistance to Staining a) Acetone (16h) b) Coffee (16h) c) 25% Sodium Hydroxide (10min) d) 30% Hydrogen Peroxide (10min) e) Shoe Polish (10min)	-	a) Rating 5 : No visible change b) Rating 5 : No visible change c) Rating 5 : No visible change d) Rating 5 : No visible change e) Rating 4 : Slight change of gloss and/or colour, only visible at certain viewing angles
11.	Lightfastness (xenon arc), 100hrs	-	Greater than grade 4
12.	Resistance to cigarette burns	-	No visible discolouration, cracks or blisters was observed

  
Ting Yeow Wah  
Associate Engineer

  
Liu Jianhong (Dr)  
Product Manager  
Polymer Products  
Mechanical Centre

**Test Report No. 7191005793-MEC11-TYW**  
**dated 30 MAY 2011**



PSB Singapore

**This Report is issued under the following conditions:**

1. Results of the testing/calibration in the form of a report will be issued immediately after the service has been completed or terminated.
2. Unless otherwise requested, this report shall contain only technical results carried out by TÜV SÜD PSB. Analysis and interpretation of the results and professional opinion and recommendations expressed thereupon, if required, shall be clearly indicated and additional fee paid for, by the Client.
3. This report applies to the sample of the specific product/equipment given at the time of its testing/calibration. The results are not used to indicate or imply that they are applicable to other similar items. In addition, such results must not be used to indicate or imply that TÜV SÜD PSB approves, recommends or endorses the manufacturer, supplier or user of such product/equipment, or that TÜV SÜD PSB in any way "guarantees" the later performance of the product/equipment. Unless otherwise stated in this report, no tests were conducted to determine long term effects of using the specific product/equipment.
4. The sample/s mentioned in this report is/are submitted/supplied/manufactured by the Client. TÜV SÜD PSB therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture, consignment or any information supplied.
5. Additional copies of the report are available to the Client at an additional fee. No third party can obtain a copy of this report through TÜV SÜD PSB, unless the Client has authorised TÜV SÜD PSB in writing to do so.
6. TÜV SÜD PSB may at its sole discretion add to or amend the conditions of the report at the time of issue of the report and such report and such additions or amendments shall be binding on the Client.
7. All copyright in the report shall remain with TÜV SÜD PSB and the Client shall, upon payment of TÜV SÜD PSB's fees for the carrying out of the tests/calibrations, be granted a license to use or publish the report to the third parties subject to the terms and conditions herein, provided always that TÜV SÜD PSB may at its absolute discretion be entitled to impose such conditions on the license as it sees fit.
8. Nothing in this report shall be interpreted to mean that TÜV SÜD PSB has verified or ascertained any endorsement or marks from any other testing authority or bodies that may be found on that sample.
9. This report shall not be reproduced wholly or in parts and no reference shall be made by the Client to TÜV SÜD PSB or to the report or results furnished by TÜV SÜD PSB in any advertisements or sales promotion.
10. Unless otherwise stated, the tests were carried out in TÜV SÜD PSB Pte Ltd, No.1 Science Park Drive Singapore 118221.

March 2010